

PM-00018⁻ 23v2

PT220





BUILT TOUGH SINCE 1981

SELF-LEVELLING BUCKET STANDARD FEATURE

Makes it impossible for the load to tip onto the operator or the machine.

PERFECTLY BALANCED

Superior design enables the loader to remain balanced either fully loaded, or with attachment removed

IMPROVED SOFT-TOUCH CONTROLS

- Smooth to drive
- Improved operator ergonomics.
- Improved safety, with safety cut-out switch if no operator is present.

LONG-LIFE LINKAGE PINS

Greasable pins ensure extended cycle life of pins and bushes.

QUICK-HITCH

Change attachments in a matter of seconds.

LARGE NON-SLIP OPERATOR PLATFORM

Wide stance for improved safety and fatigue reduction. Rubber mounted platform reduces vibrations for better comfort.

FULL FLOW AUXILIARY

Hydraulic power outlet.

AVAILABLE IN BOTH WHEEL & TRACK WITH OVER 6" OF GROUND CLEARANCE

Choice of heavy duty tracks or wheels.

POWERFUL 20HP HONDA ENGINE

OPERATOR CAPSULE

Padded to maintain operator comfort and safety.



ENGINEERED FOR SAFE, USER-FRIENDLY OPERATION AND PEACE OF MIND.

Since inventing the mini loader in 1981, Kanga has continued to lead the industry in **safety, innovation**, and **performance**. Kanga Loaders adheres to Occupational Health & Safety government guidelines, and operates under world's best practices.



OPERATOR CAPSULE

NEW - Padded rear protection and operator stability extension.



NARROW ACCESS

With an overall width of 30.2in (wheeled) / 32.3in (tracked), you can access the worksite through side gates and standard doorways.



QUICK HITCH

Specially designed for the 2 Series Loader.



SAFETY RELIEF VALVE

The lift circuit is set at 1500psi to protect the operator from overloading the machine, and is located on the machine's rear, for ease of access.



OVER 6" OF GROUND CLEARANCE WHILE MAINTAINING A LOW CENTER OF GRAVITY

When the loader arms are lowered to rest on the frame the bucket can be rolled back to carry a full load while maintaining ground clearance and a lower center of gravity.



TRAVERSE OVER UNDULATING GROUND

Crawl over gutters and uneven terrain with confidence. Unlike other brands with fixed under-carriage track systems, Kanga's stable wrap-around tracked system will not pivot whilst traversing over undulating ground.

2 SERIES ATTACHMENTS

POWER HEAD | 0K30401

Driving head for augers with overall diameters between 4" (100mm) - 18" (450mm), as well as mixer bowl. Comes with tow ball and ripper.



MIXER BOWL | KA-000008

Convert your Kanga into a mobile concrete mixer. No more hauling materials to the mixer or concrete to the job. Easily lift and place concrete over low walls or into post holes etc. Requires an Auger Power Head attachment (0K30401).



AUGERS

Available with Tungsten carbide tip pilots with Earth, Tungsten Carbide, or Multi-faceted Tungsten teeth, in single or double cutting head configurations. Choose from diameters between 4" (100mm) and 18" (450mm). Tree augers also available with a root ball of up to 20" (500mm).



AUGER EXTENSION |

I-KIDEXT-300-K

Fits between the power head and auger, to increase digging depth.



STANDARD BUCKET | 0K11630

Open shape helps prevent sticky materials from clogging. Volume sized to rated load capacity cannot be exceeded when brim filled with heavy materials, wet sand or gravel, Ideal for everyday use, shifting sand and soil, clean up and backfill. Heaped volume: 2.72cu ft / 0.077m³.



4 IN 1 BUCKET | 0K60063

Enables front blading, back blading, plus all the advantages of a regular bucket. Open jaws to dump at full height. Use jaws for stump, post and tent peg pulling, lifting, placing rail road ties and rocks, broken tree limbs & broken concrete etc. Heaped volume: 2.97cu ft 0.084m³.



MULCH BUCKET | DK50135

For handling bulky, light materials such as bark chips, mulch and sawdust, quickly and easily. Straight cutting edge to scrape floors clean. Use in horse stables, stud farms and feed lots etc. Heaped volume: 4.06cu ft /0.115m².



RUBBLE BUCKET | OK50191

Ideal for preparing difficult rocky soil for sod and turf. For removal of unwanted rocks and sticks, leaving soil behind. Makes light work of the most difficult site conditions. A grapple attachment is also available.



GRAPPLE BUCKET | OK50189

Comes fitted with a hydraulically operated grapple attachment. With its front jaw, the grapple teeth can be used for holding onto material, or making the bucket more effective at managing tree limbs, straw, hay, and more.



A VAST SELECTION OF ATTACHMENTS ARE AVAILABLE SPECIFICALLY FOR THE 2 SERIES, ENABLING YOU TO COMPLETE THE TOUGHEST JOBS QUICKLY AND EASILY.

CHECK WEBSITE FOR MORE ATTACHMENTS

LAWN AERATOR |

OKSO405

Rejuvenates old tired lawns, and reduces compaction. The holes created by the aerator allow oxygen, water, and nutrients into the soil profile which stimulate better grass growth. 30" (765mm) wide.



BUCKET BROOM

OK50303

Clean up all manner of debris and leave your construction site clean. Self loading bucket, ideal for side walks, parking lots, factories, industrial sites and feed lots etc. Reverse rotation to push snow and gravel. Broom swings away automatically as bucket is emptied.



TURF CUTTER | 0K50180

With only one moving part (front roller), the turf cutter is a low maintenance attachment which provides stability to set the required cutting depth, and effortless control for removing old turf, transplanting sod, and removing turf prior to trenching. Cutting width: 12" (300mm).



TRENCHER |

DK42025

24" (600mm) maximum depth, 4" (100mm) width. Ideal for irrigation, garden lighting, drainage trenches.



CARRYALL LEVELLER

OK50110

For transporting bulky items, paving tiles, cement bags, nursery plants, sod, turf and fence palings. Ideal for preparing top soil for sod or turf laying and levelling bedding sand for pavers. 35" (900mm) wide.



MULTITOOL BAR CARRIER

OK50063

The Multitool Bar Carrier features a 'quick attach' system that will have compatible Kanga tools in place in mere seconds. The Multitool Bar Carrier can be used with the Tow Hitch, and Forks.



HYDRAULIC ANGLE BLADE

OK85003

Backfill Blade ideal for backfilling trenches, pushing loose soil, feed lot clean-out. Fingertip hydraulic controlled side shift tilts blade from left to right. 39" (1000mm) wide.



RIPPER/HOOK | 0K30403

Ideal for ripping hard ground before digging with a bucket, and can also be used as a lifting hook. A tow ball can also be attached to the frame for towing.



ROTARY TILLER I

OK83701

Heavy duty tiller turns the toughest ground into beautiful garden beds. Perfect for sod and turf bed preparation. Cuts 4.5" (120mm) deep, and 30" (750mm) wide.



VINYL STRIPPER

OK50220


Quickest way to remove floor coverings - including vinyl, carpet, wooden floors, and even scraping the adhesive used.



2 SERIES







The above graphic is intended for illustrative purposes only.

- ¹ Tipping load and Rated Operating Capacity (ROC) have been determined to ISO 14397-1 though the values shown here need to be adjusted for specific attachments. Refer to the section of the Operators Manual "Practice Safety at All Times" for Tipping Load and ROC values for the range of Kanga bucket and fork attachments. Note that ROC is 50% of the Tipping Load for wheel loaders and 45% for Kanga "over tire track" loaders.
- ² Machine Weight is calculated with no operator, using no bucket, full fuel tanks, and air-filled tires. Weight will differ depending on model and options.
- ³ Power Rating is the gross power of the production engine, only as measured in accordance with SAE J1995 at 3600 RPM. Mass production engines vary from this value. Actual power output for the engine installed in the delivered machine may vary, depending on numerous factors. These factors can include engine operation in the application, environmental conditions, and other variables.

PERFORMANCE

Tipping Load1 (No Bucket)

Rated Operating Capacity (AOC)1 No Bucket

Maximum Travel Speed (Fast Mode)

Fuel Capacity (Petrol)

Loader Mass²

ENGINE

Manufacturer

Rated Power

DRIVE SYSTEM

Drive Control

Throttle Control

Wheels with Direct Drive Hydraulic Motor

HYDRAULICS

Gear Pump Displacement

Pump output

System Pressure

Hydraulic Reservoir Capacity

BUCKETS

HD 4in1 Bucket Capacity (heaped/ struck)4

DIMENSIONS

A Max Operating Height

B Height to Hinge Pin

C Overall Height (No Warning Lights)

D Overall Length With 4in1 Bucket

E. Overall Track width

F Bucket Reach at 40° (4in1 Bucket)

H Angle of Departure

I Max Roll Back

J Bucket Width (4in1 Bucket)

K Overall Length Less Bucket

L Ground Clearance

	TRACKS	WHEELS
	PT220	PW220
	794 lbs	785 lbs
	357 lbs	392 lbs
	3.4 mph	3.4 mph
	3.06 US gal	3.06 US gal
	1040 lbs	980 lbs
	Honda GXV630 (Petrol)	Honda GXV 630 (Petrol)
	20.8 HP	20.8 HP
	Soft Touch Hand Levers - Rubber Mounted	Soft Touch Hand Levers - Rubber Mounted
	Hand Levers	Hand Levers
	Rear Wheels (x2)	Rear Wheels (x2)
	0.488 cu in/rev	0.488 cu in/rev
	6.7 US gal/min	6.7 US gal/min
	3000 PSI	3000 PSI
	13.6 US gal	13.6 US gal
3		
	2.97 CU ft/2.23 CU ft	2.97 CU ft/2.23 CU ft
	59.2"	58.7"
	47"	46.5"
	50.9"	50.5"
	78.2"	78.2"
	31.1"	29.7"
	6.9"	7.4"
	34°	34°
	38°	38°
	31.9"	31.9"
	60.2"	60.2"
	6.5"	6.1"



GET THE BEST FROM YOUR KANGA WITH OPTIONAL ADD-ONS...



LED Headlights.



Reverse Beeper.



Horn - often required for Operational Health & Safety.



Flashing Amber Beacon Light - often required for Operational Health & Safety.



Emergency Stop Button - shuts down the machine functions in the event of an emergency.



Back Protection Bars - an extension of the safety cell used to encapsulate the operator when operating in confined spaces, protecting the rear of the machine from unnecessary damage.



Battery Isolator Switch - non-lockable isolator.

THE WORLD'S SMALLEST STAND-ON MINI LOADER

The Kanga 2 Series is Kanga's smallest multi-task compact skid steer loader. Fitted with a special range of Kanga attachments, you can complete the toughest jobs quickly and easily. With residential site access becoming increasingly smaller, the 2 Series is the popular choice among landscapers, pool installation, builders, contractors, plumbing, electrical contractors, and many more.



HONDA COMMERCIAL V-TWIN ENGINE

Honda is the world's largest engine manufacturer producing small engines since 1953. The GVX630 is a 4-stroke 2 cylinder engine with exceptional economy and cooling power. The 36 blade high capacity cooling fan coupled with race inspired connecting rods, integrated cylinder and head also aid in lowering vibrations and result in quieter operation.



The original idea which led to the world's first stand- on machine, was originally a motorized wheelbarrow.

By 1980, the concept developed into a walkbehind machine with similar design and styling characteristics, found on modern machines.

The first standon machine was introduced to the world. Named the Riga'l Universal Loader, it was powered by an 11hp motor.

The loaders were renamed the Jaden Loader. A larger sized model was released, named the Dingo 1000.

The Jaden Maxi prototype was powered by a 16hp Engine. Only 35 were ever made.



The 5 Series model saw an introduction to soft-touch controls, auxiliary cutout, and redesigned fuel tanks, in preparation for the introduction of tracks.

The 2 Series was released, to align with the original concept of a tight access and affordable earthmoving solution.

The Kid track mini loader was released, as the smallest tracked machine in the world.

6 & 7 Series mini loaders were released. Originally named the Big Foot, due to its 12" wheels, available in a 24hp petrol, or 20hp Diesel engine. The Track machine was named Fat Track.

A new 25hp 2-speed 8 Series loader, featuring an oil cooler, trenching valve, and auto quick-hitch release - The largest and most powerful in the range.



The Kanga 8 Series range, featuring a 25hp diesel motor, was released. Available in wheeled and tracked versions.

Kanga release the Kanga Klean program as an industry-first in emissions reduction.

Kanga release the DT835 as the most powerful Kanga mini loader.

Kanga Loaders launches in North America - USA.

Kanga Loaders celebrates its 40th year anniversary.



MK1 - A major chassis design revision was undertaken to increase power and improve poise & balance.

Long range fuel tanks were added over the wheels. Power was increased to 16hp.

3 Series - Optional 10" wheels, larger fuel tanks (which encapsulate the operator), and the iconic green colour were introduced. Received 'Australian International Design' Award.

4 Series - First model with 10" wheels as standard. Petrol and Diesel model options became available.

Kanga begins exports to North America and New Zealand.



upgraded to 4-wheel motors, a wider platform, and an increase of performance and comfort. Received 'Innovative Product of the Year' Award.

Remote Loader commences development, and first prototype released.

Kanga Loaders was acquired by Digga Australia. The manufacturing of loaders was moved into the Digga factory.

The Kanga Warrior was released.
A cost effective bare-bones model for the weekend warrior.

Remote Loader was released, with wheeled and track versions available.



Logo and machine branding modernised.

KANGA LOADERS

MULTI-TASKING MADE EASY

Since being established in 1978 as Jaden Engineering, the Kanga loader has been a source of innovation for the multi-task compact skid steer market. Upholding the highest safety industry standards, starting with the original idea and prototype in 1980, Kanga later developed the first production model in 1981. Kanga Loaders has since become an Australian household name within the mini loader industry.



TURNING HARD WORK INTO EASY BUSINESS SINCE 1981

PHONE 833 30KANGA

EMAIL infous@kangaloader.com



WARRANTY



ENGINE

3 YEARS/UNLIMITED

Gas machines

COMMERCIAL PRODUCT

5 YEARS

Chassis structure.

2 YEARS/1,000 HOURS

Arm/tilt assembly workmanship and structure.

1 YEAR

Other components and electrical. Warranty Conditions Apply.